

Tyre Size	PR	Tread design				Rim Fitment (1)		Tube	Tyre Dimensions max in service (2)		Inflation Pressure	Load capacity (3)			
		SD SKS CLASSIC	SD SKS XTRA	HA SKS	HA SKZ										
		Rec	Alternative	Width [mm]	O.D [mm]	(+/-15%) [bar]	8 km/h [kg]		16 km/h [kg]	Creep (4) [kg]	Static [kg]				
5.70-12	6	■		■◆		4.50I	5JA	TBLS	157	585	4.20	660	520	760	1040
23x8.5-12	6	■		■		7.00I	7JA	TBLS	231	589	3.50	825	650	950	1300
	10	■		■							5.90	1110	880	1280	1750
	12	■		■							7.00	1235	980	1420	1950
26x12-12	8	■				10.50	8.50/8.50 JA	TBLS	307	648	3.50	1370	1080	1580	2160
	10	■									4.50	1630	1290	1870	2580
27x10-12	14	■				8.00G		TT	275	704	7.00	3545	3215	4080	4115
7.00-15	6	■				5.50	6 LB	TBLS	223	808	4.10	1440	1140	1660	2280
27x8.5-15	6	■		■		7JA	6.5 K/7J	TBLS	231	695	3.50	1030	810	1180	1630
	8	■					6.5 K				4.10	1110	880	1280	1750
27x10.5-15	8			■		8.50	8 LB	TBLS	259	695	4.10	1160	920	1330	1830
	8	■		■							3.10	1690	1340	1940	2670
31x15.5-15	10			■		13.00	13 LB	TBLS	391	788	4.10	1985	1570	2280	3140
	12			■							5.25	2230	1760	2560	3520
	8			■							4.20	1875	1480	2160	2960
10-16.5(30)	10			□		8.25		TBLS	285	760	5.25	2140	1690	2460	3380
10-16.5	6	■	■			8.25		TBLS	285	788	3.15	1590	1260	1830	2510
	8	■	■	■	■						4.20	1875	1480	2160	2960
	10	■	■	■	■						5.25	2140	1690	2460	3380
31.5x13-16.5	10			■		9.75			353	800	4.90	2435	1920	2800	3850
12-16.5	8	■	■	■		9.75		TBLS	332	848	3.50	2180	1720	2510	3440
	10	■	■	■	■						4.50	2545	2010	2930	4020
	12			■	■						5.60	2880	2280	3310	4550
33x15.5-16.5	12			■		12.00		TBLS	424	838	4.10	2900	2290	3340	4580
	14			■	□						4.90	3150	2490	3620	4980
14-17.5	10	■	■	■	□	10.5		TBLS	388	954	3.85	3105	2450	3570	4910
	12	■	■								4.80	3550	2800	4080	5610
	14			■	□						5.60	3875	3060	4460	6120
380/65-19.5(14.5-19.5)	12			□		11.75	12.25	TBLS	431	991	4.20	4170	3290	4800	6590
	14			■◆							5.60	5070	4010	5830	8010
	16			■◆							7.00	6000	4740	6900	9480
15-19.5	8			□		11.75	12.25	TBLS	431	1056	2.80	3255	2570	3740	5140
	10			■							3.50	3745	2960	4310	5920
	12			■							4.20	4170	3290	4800	6590
	14			■							5.60	5070	4010	5830	8010
	16			■							7.00	6000	4740	6900	9480
385/65-22.5(15-22.5)	16			■		11.75	12.25	TBLS	408	1102	7.00	7040	5560	8100	11120
	20			■							9.00	8325	6580	9570	13150

■	Available
□	Available later 2002
■◆	On request only
Also available in All White and Electrically Conducting	

- REMARKS (1) Consult tyre and wheelmanufacturer for confirmation of the suitability of the tyre / rim combination particularly with regard to rim profile, wheel strength and maximum inflation pressure.
- (2) The sizes given are according to ETRTO or TRA, where available.
For exact sizes, please consult the technical department.
- (3) For skid-steer and mini-loader service.
- (4) Creep speed is a travel rate of not over 60 m in a 30 minute period.



SD SKS Classic SD SKS XTRA HA SKS HA SKZ Lifemaster

DISTRIBUTED BY